


## 仕様諸元表

使用荷重 (t)	チェーン線径 (mm)			形式	寸法 (mm)				質量 (kg)
	S	D	T,Q		p	a	d	t	
1.1	ø6	-	-	HMG0807	225	112	17	14	1.2
1.5	ø7	-	-						
1.7	-	ø6	-						
2.0	ø8	ø7	ø6	HMG1008			20	17	1.6
3.2	ø10	ø8	ø7				23	20	
5.0	ø13	ø10	ø8	HMG1310			36	29.5	8.1
8.0	ø16	ø13	ø10	HMH1613	340	180	40	34.5	10.1
11.5	ø20	ø16	ø13	HMH2016					



◎チェーン線径S、D、TQはつり本数を表します。S:シングルスリング、D:ダブルスリング、TQ:トリプルおよびクォードスリング

## 大型マスターリンクHMG/HMHに使用するハイカップリングの組合せ

つり方	使用荷重 (t)	チェーン線径 (mm)	マスターリンク	ハイカップリング		状態図
1本つり	1.1	ø6	HMG0807	HC3080	HC3060	①
	1.5	ø7	HMG0807	HC3080	HC3070	
	2.0	ø8	HMG0807	HC3080	-	②
	3.2	ø10	HMG1008	HC3100	-	
	5.0	ø13	HMG1310	HC3130	-	
	8.0	ø16	HMH1613	HC3160	-	
	11.5	ø20	HMH2016	HC3200	-	
2本つり	1.7	ø6	HMG0807	HC3080x2	HC3060x2	③
	2.0	ø7	HMG0807	HC3080x2	HC3070x2	
	3.2	ø8	HMG1008	HC3080x2	-	④
	5.0	ø10	HMG1310	HC3100x2	-	
	8.0	ø13	HMH1613	HC3160x2	HC3130x2	⑤
	11.5	ø16	HMH2016	HC3200x2	HC3160x2	
3本つり	2.0	ø6	HMG0807	HC3080x2	HC3060x3	⑥
	3.2	ø7	HMG1008	HC3080x2	HC3070x3	
	5.0	ø8	HMG1310	HC3100x2	HC3080x3	
	8.0	ø10	HMH1613	HC3160x2	HC3100x3	
	11.5	ø13	HMH2016	HC3200x2	HC3130x3	
4本つり	2.0	ø6	HMG0807	HC3080x2	HC3060x4	⑦
	3.2	ø7	HMG1008	HC3080x2	HC3070x4	
	5.0	ø8	HMG1310	HC3100x2	HC3080x4	
	8.0	ø10	HMH1613	HC3160x2	HC3100x4	
	11.5	ø13	HMH2016	HC3200x2	HC3130x4	

